



MARUMA

MSW-6S

Code No. CE-0301

MSW-6L

Code No. CE-0303

SHOE BOLT IMPACT WRENCH



For fast loosening and tightening of the shoe bolt of the track link assembly, the powerful and economical MSW series Shoe Bolt Impact Wrenches are available for the toughest jobs. By utilizing a Shoe Bolt Impact Wrench, the expensive bolts may be reused, instead of being thrown away, as in the case of torch cutting.

The MSW-6S is applicable to shoe bolts up to of Cat D9 and Komatsu D355 class models.

The MSW-6L is applicable even to shoe bolts of Cat D11N and Komatsu D475 class models.

FEATURES

- **One-Man Operation**

MSW-6S & 6L Shoe Bolt Impact Wrenches have been specifically designed and engineered for one-man operation for both disassembly and assembly of track shoe bolts.

- **Powerful and Speedy**

MSW-6S & 6L have sufficient power to twist off heads of rusted hard-to-remove bolts, 50% faster and more powerful than the regular impact wrenches.

- **Easy Operation**

Finger tip control permits instant forward-reverse and stop operation, permits one-man operation.

- **Saves Power Cost**

Special high torque 2.2kW motor saves electric power cost. If an air impact wrench, of comparable capacity of an MSW-6S, is used, at least a 22kW compressor or larger would be required.

- **Drawing Available**

The shoe bolt wrench comes complete with a heavy-duty wrench carrier. The drawings of the rail stand and roller conveyer are available, for local fabrication, upon request.

SPECIFICATIONS

	MSW-6S	MSW-6L
Electric Motor:	2.2 kW, 190-230 V / 380-460 V	3.7 kW, 190-230 V / 380-460 V
Torque:	5960 N·m (608kg·m.) in 10 sec.	8820 N·m (900kg·m.) in 10 sec.
Spin Speed:	Approx. 400 min ⁻¹ (rpm)	Approx. 500 min ⁻¹ (rpm)
Drive square:	1½"	1½"
Dimensions (LxWxH):	2.2 m x 1.12 m x 1.16 m	2.2 m x 1.12 m x 1.16 m
Net weight:	Approx. 250 kg.	Approx. 260 kg.
Standard accessory:	Socket adapter to fit 1" square drive sockets	Socket adapter to fit 1" square drive sockets

Specifications and illustrations are subject to change without notice.



MARUMA TECHNICA CO., LTD.

NO. 2-1, OHNODAI 6-CHOME, SAGAMIHARA CITY, KANAGAWA PREF. 229-0011 JAPAN
TEL: 81-42-751-3024 FAX: 81-42-751-9065 E-mail: overseas@maruma.co.jp