

# PIN PULLER



Single acting return hydraulic jacks are available in both alloy steel and aluminium and have 50 and 100mm stroke which pin, and bush can be replaced in one or multiple strokes. Jacks are centre hole type and are places on C-sleeves (one over the other) through which centre rod passes and nuts are tightened at the ends. Tie rods and nuts are machined from an alloy steel material, hardened, and tempered to increase strength and toughness.

## Safety Features:

- The spring balancer fitted on the trolley allows for the simple hands free operation.
- Saving in time and labour.
- Adopted by both repair shops and OEM's.
- Suitable for onsite repairs.
- Suits most of the construction machineries and brands.
- Safe compared to traditional methods.
- Aluminium alloy for light weight and easy handling.

**This trolley is an optional accessory that makes for precise and accurate operation of the pin puller**



Model	Stroke (mm)	Closed height (mm)	Outer diameter (mm)	Bore diameter (mm)	Ram diameter (mm)	Centre hole (mm)	Effective area (sq cm)
HE PP 30/50	100	245/255	115/150	95/135	80/110	33/42	42.6/78.5
HE PP 100	100	295	215	180	150	77	141.40
HE PP 150	100	325	245	200	150	80	235.6
HE PP 200	100	350	290	220	160	80	235.6